



MODEL NAME		P 75 F	P 75 H	P 75 K	P 75 M
Wheelbase	X	2900 ⁵	3365	3815	4475
Overall length	K	5575	6040	6690	7870
Body length min ¹	W	3810	4275	4925	6105
Body length max ¹	W	4125	4590	5240	6420
Rear overhang	Y	1560	1560	1760	2280
Chassis height (unladen)	T	800			
Overall height (unladen)	H	2265			
Rear axle width	L	2115			
Cab width ²	L1	2040			
Body width ³	C	2345			
Front axle to back of cab	Dmin	650			
Front overhang	A	1110			
Frame internal size	I	850			
Front track	C1	1680			
Rear track	C2	1650			
Minimum Road Clearance	-	210			
WEIGHT (kg)					
Unladen weight ⁴		2620	2620	2640	2695
Unladen weight front axle		1665	1665	1695	1765
Unladen weight rear axle		995	955	945	930
Minimum weight vehicle equipped					
Gross vehicle weight		7500			
Front/rear total weight		3100 / 6000			
Max trailer weight unbraked/braked		750 / 3500			
<ol style="list-style-type: none"> 1. The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications). 2. Excluding turn signal and side mirrors 3. Possible widths with optional mirror brackets 2040/2170 – 2170/2345 – 2345/2500 4. The Unladen weight include spare wheel, full fuel tank and driver 75 kg. AMT: +35 kg (25/10) 5. Wheelbase modified 					

W/B (mm) F 2900 - H 3365 - K 3815 - M 4475

2017

Equipment	Automated transmission NEES 2 Guida a destra (W/B H e previo accordo disponibilità e tempi di consegna)	
Standard features	<ul style="list-style-type: none"> • EGR – DPD (Diesel particulate diffuser) • SCR con Ad-Blue® • Multi information display • Engine exhaust brake • Side mirrors heated and electric <ul style="list-style-type: none"> • Warning reverse • Immobilizer • Central locking with remote control • Electric windows • Suspension seat <ul style="list-style-type: none"> • Radio with USB • Fog lamps • Head lamps control leveling • Daytime running line • Steering wheel adjustable • Speed limiter (90km/h) 	
Optional equipment	Air conditioning	
Engine	ISUZU 4JJ1E6N Diesel, 4 cylinders 16-valve, common rail direct-injection intercooler with Variable-geometry turbocharger. Displacement 2999 cm ³ Power max 110kW (150 HP) at 2800 giri/min Torque max 375 Nm/1600 – 2800 giri/min Emission level EURO VI update OBD-C	
Tank capacity	ABS ESC – Electronic stability control with ASR LDWS – Lane Departure Warning System SRS air-bags driver and passenger	
Safety system	Lt 90	Lt 16 Ad-Blue®
Transmission ratios	6 gear MYY6S – 5.979 - 3.434 - 1.832 - 1.297 - 1.000 - 0.759; Reverse 5.068; Final gear ratio 5.571 (39/7)	
Transmission control	MANUAL	NEES 2 – Automated T/M
Frame dimension	Width 70 mm, height 216 mm, thickness 6 mm	
Seat number	3	
Tire	215/75 R17,5, with rear twin wheels	
Brake	Front and rear: ventilated discs with asbestos-free linings. Mechanical drum brake rear of transmission. Brake type: ABS divided hydraulic, vacuum servo assisted with electronic brake distribution.	
Suspension	Front and rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.	
Electrical system	Tensione nominale a 24V - Alternator 90A, Nr. 2 battery 100 Ah	