



MODEL NAME		P 75 F	P 75 H	P 75 K	P 75 M	P 75 Q
Wheelbase	X	2900 ⁵	3365	3815	4475	5300 ⁵
Overall length	K	5570	6040	6690	7870	9250
Body length min ¹	W	3750	4215	4865	6045	7430
Body length max ¹	W	4065	4530	5180	6360	7745
Rear overhang	Y	1560	1560	1760	2280	2840
Chassis height (unladen)	T	800				
Overall height (unladen)	H	2265				
Rear axle width	L	2115				
Cab width ²	L1	2040				
Body width ³	C	2345				
Front axle to back of cab	Dmin	710				
Front overhang	A	1110				
Frame internal size	I	850				
Front track	C1	1680				
Rear track	C2	1650				
Minimum Road Clearance	-	210				

WEIGHT (kg)						
Unladen weight ⁴		2830	2830	2850	2905	3025
Unladen weight front axle		1840	1830	1860	1930	1970
Unladen weight rear axle		990	1000	990	975	1055
Minimum weight vehicle equipped						
Gross vehicle weight		7500				
Front/rear total weight		3100 / 6000				
Max trailer weight unbraked/braked		750 / 3500				

- The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
- Excluding turn signal and side mirrors
- Possible widths with optional mirror brackets 2040/2170 – 2170/2345 – 2345/2500
- The Unladen weight include spare wheel, full fuel tank and driver 75 kg. AMT: +35 kg (25/10)
- Wheelbase modified

W/B (mm) F 2900 - H 3365 - K 3815 - M 4475 - Q 5300

2017

Equipment	Automated transmission NEES 2 con Cruise Control Guida a destra (W/B H e previo accordo disponibilità e tempi di consegna)	
Standard features	<ul style="list-style-type: none"> • EGR – DPD (Diesel particulate diffuser) • SCR con Ad-Blue® • Multi information display • Engine exhaust brake • Side mirrors heated and electric 	
	<ul style="list-style-type: none"> • Warning reverse • Immobilizer • Central locking with remote control • Suspension seat • Radio with USB 	<ul style="list-style-type: none"> • Fog lamps • Head lamps control leveling • Daytime running line • Electric windows • Steering wheel adjustable • Speed limiter (90km/h)
Optional equipment	Air conditioning	
Engine	ISUZU 4HK1E6C Diesel, 4 cylinders 16-valve, common rail direct-injection intercooler with Variable-geometry turbocharger. Displacement 5193 cm ³ Power max 140kW (190 HP) at 2600 giri/min Torque max 510 Nm/1600 – 2800 giri/min Emission level EURO VI update OBD-C	
Tank capacity	ABS ESC – Electronic stability control with ASR LDWS – Lane Departure Warning System SRS air-bags driver and passenger	
Safety system	Lt 90	Lt 16 Ad-Blue®
Transmission ratios	6 gear MZZ6F 6.369 - 3.767 - 1.966 - 1.355 - 1.000 - 0.782; Reverse 6.369; Final gear ratio 4.100 (41/10)	
Transmission control	MANUAL	NEES 2 – Automated T/M
Frame dimension	Width 70 mm, height 216 mm, thickness 6 mm	
Seat number	3	
Tire	215/75 R17,5, with rear twin wheels	
Brake	Front and rear: ventilated discs with asbestos-free linings. Mechanical drum brake rear of transmission. Brake type: ABS divided hydraulic, vacuum servo assisted with electronic brake distribution.	
Suspension	Front and rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.	
Electrical system	Tensione nominale a 24V - Alternator 90A, Nr. 2 battery 100 Ah	